

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application:

LISTING OF CLAIMS:

1. (original): A fluorescent-light image obtaining apparatus comprising
excitation light emitting means for projecting excitation light onto a target tissue, and
illuminating light emitting means for projecting illuminating light onto the target tissue,
and
fluorescent-light image obtaining means for obtaining a fluorescent-light image formed
of the fluorescent-light emitted from the target tissue upon irradiation thereof by the excitation
light, and
a normal-image obtaining means for obtaining a normal-image formed of the illuminating
light reflected from the target tissue upon irradiation thereof by the illuminating light, further
comprising
a contact detecting means for detecting that the distal end of excitation light emitting
means has come into contact with the target tissue, and
an excitation light emission controlling means for controlling, in response to the detection
signal of said contact detecting means, the output of the excitation light emitted from the
excitation light emitting means.

2. (original): A fluorescent-light image obtaining apparatus as defined in claim 1, wherein the excitation light emission control means is a current controlling means for controlling the current occurring in the excitation light source.

3. (original): A fluorescent-light image obtaining apparatus as defined in claim 1, wherein said excitation light emission controlling means causes the emission of the excitation light from the excitation light emitting means to stop.

4. (original): A fluorescent-light image obtaining apparatus as defined in claim 1, wherein said excitation light emission controlling means causes the excitation light from the excitation light emitting means to be emitted at an intensity below a predetermined value.

5. (original): A fluorescent-light image obtaining apparatus comprising excitation light emitting means for projecting excitation light onto a target tissue, and illuminating light emitting means for projecting illuminating light onto the target tissue, and

fluorescent-light image obtaining means for obtaining a fluorescent-light image formed of the fluorescent-light emitted from the target tissue upon irradiation thereof by the excitation light, and

a normal-image obtaining means for obtaining a normal-image formed of the illuminating light reflected from the target tissue upon irradiation thereof by the illuminating light, further comprising

a distance parameter detecting means for detecting a parameter correlating the distance between the distal end of excitation light emitting means and the target tissue, and

an excitation light emission controlling means for controlling, based on the parameter detected by the distance parameter detecting means, the output of the excitation light emitted from the excitation light emitting means.

6. (original): A fluorescent-light image obtaining apparatus as defined in claim 5, wherein the parameter is based on the light intensity of the fluorescent-light image obtained by the fluorescent-light image obtaining means.

7. (original): A fluorescent-light image obtaining apparatus as defined in claim 6, wherein the parameter is based on the pixel values of the entire image or a predetermined portion of a fluorescent-light image obtained by the fluorescent-light image obtaining means.

8. (original): A fluorescent-light image obtaining apparatus as defined in claim 5, wherein the parameter is the light intensity of the normal-image obtained by the normal-image obtaining means.

9. (original): A fluorescent-light image obtaining apparatus as defined in claim 8, wherein the parameter is based on the pixel values of the entire image or a predetermined portion of a normal-image obtained by the normal-image obtaining means.

10. (original): A fluorescent-light image obtaining apparatus as defined in claim 5, further comprising

reference-light emitting means for projecting a reference-light onto the target tissue, and reflected-light image obtaining means for obtaining a reflected-light image reflected from the target tissue upon irradiation thereof by the reference-light, wherein

said parameter is based on the light intensity of the reflected-light image obtained by the reflected-light image obtaining means.

11. (original): A fluorescent-light image obtaining apparatus as defined in claim 10, wherein

the parameter is based on the pixel values of the entire image or a predetermined portion of a reflected-light image obtained by the reflected-light image obtaining means.

12. (original): A fluorescent-light image obtaining apparatus as defined in claim 5, wherein

the excitation light emission control means is a current controlling means for controlling the current occurring in the excitation light source.

13. (original): A fluorescent-light image obtaining apparatus as defined in claim 5,
wherein

said excitation light emission controlling means causes the emission of the excitation
light from the excitation light emitting means to stop.

14. (original): A fluorescent-light image obtaining apparatus as defined in claim 5,
wherein

said excitation light emission controlling means causes the excitation light from the
excitation light emitting means to be emitted at an intensity below a predetermined value.

15. (new): The fluorescent-light image obtaining apparatus as defined in claim 1,
wherein a strength of the excitation light is controlled at the same time as the strength of the
illuminating light.

16. (new): The fluorescent-light image obtaining apparatus as defined in claim 5,
wherein a strength of the excitation light is controlled at the same time as the strength of the
illuminating light.